Beta-Pak

Available Range /
Kullanım Aralıkları

Thermoform Packaging
Machines with Chain
Zincirli Termoform Ambalaj Makineleri

	Bpz Jr	Z 105	Bpz 400	Bpz 400 Max	Joy Box Line		Bpz Medical
					Joy Box Line	Bpz 400	
Applications Ürün Tipi	Sausage, Cheese, etc. Sosis, Sucuk, Peynir, vb.	Sausage, Cheese, etc. Sosis, Sucuk, Peynir, vb.	Dairy Desserts, Bakery Products, etc. Sütlü Tatlılar, Unlu Mamüller vb.	Dairy Desserts, Bakery Products, etc. Sütlü Tatlılar, Unlu Mamüller vb.	Suprise Egg - Toy Süpriz Yumurta - Oyuncak	Suprise Egg - Toy Süpriz Yumurta - Oyuncak	Medical Products, Drugs, etc. Medikal Ürünler, İlaçlar, vb.
Capacity Kapasite	5 - 7 cycle/min. 5 - 7 vuruş/dk.	6 - 8 cycle/min. 6 - 8 vuruş/dk.	6 - 12 cycle/min. 6 - 12 vuruş/dk.	6 - 12 cycle/min. 6 - 12 vuruş/dk.	18 - 20 cycle/min. 18 - 20 vuruş/dk.	18 - 20 cycle/min. 18 - 20 vuruş/dk.	10 - 14 cycle/min. 10 - 14 vuruş/dk.
Packaging Type	Map/Simple Hermetic/Vacuum	Map/Simple Hermetic/Vacuum	Map/Simple Hermetic/Vacuum	Map/Simple Hermetic/Vacuum	-	-	Simple Hermetic / Vacuum
Shape Depth Şekil Derinliği	max. 75mm.	max. 90mm.	Standart: max. 80mm. Special: max. 150mm. Standart: max. 80mm. Özel: max. 150mm.	max. 80mm.	-	max. 40mm.	max. 80mm.
Film Widths Film Genişliği	200 - 422mm.	250 - 422mm.	250 - 460mm.	250 - 600mm.	250 - 400mm.	250 - 400mm.	250 - 462mm.
Film Thickness Film Kalınlığı	100 - 200µm.	120 - 700µm.	120 - 1200µm.	120 - 1200µm.	-	-	80 - 700µm.
Bottom Film Alt Film	PA+PE	PA+PE / PVC+PE / PET+PE	PA+PE / PVC+PE / PET+PE	PA+PE / PVC+PE / PET+PE	PVC+PE / PET+PE	PVC+PE / PET+PE	PA+PE / PVC+PE / PET+PE
Top Film (customizable) Üst Film (özelleştirilebilir)	PA+PE	PA+PE	PA+PE	PA+PE / ALU / PAPER+PE	-	PA+PE	PA+PE / ALU / PAPER+PE / MED. PAPER / TYVEK+PE
Reel Diameter Bobin Çapları	Bottom: max. 300mm. Top: max. 200mm. Alt: max. 300mm. Üst: max. 200mm.	Bottom: max. 400mm. Top: max. 300mm. Alt: max. 400mm. Üst: max. 300mm.	Bottom: max. 400mm. Top: max. 300mm. Alt: max. 400mm. Üst: max. 300mm.	Bottom: max. 400mm. Top: max. 300mm. Alt: max. 400mm. Üst: max. 300mm.	Bottom: max. 400mm. Top: max. 300mm. Alt: max. 400mm. Üst: max. 300mm.	Bottom: max. 400mm. Top: max. 300mm. Alt: max. 400mm. Üst: max. 300mm.	Bottom: max. 400mm. Top: max. 300mm. Alt: max. 400mm. Üst: max. 300mm.
Reel Core Diameter Bobin Göbek Çapı	76mm.	76mm.	76mm.	76mm.	76mm.	76mm.	76mm.
Machine Dimensions (approx) Makine Ölçüleri (yaklaşık)	2750x1200x2000mm.	4750mm.	5750x8000mm.	6000x12000mm.	5000mm	6000x12000mm.	5000x12000mm.
Stations Drive Type İstasyonlar Tahrik Tipi	Piston Pistonlu	Piston Pistonlu	Serve Engine / Piston Servolu / Pistonlu	Serve Engine / Piston Servolu / Pistonlu	Serve Engine / Piston Servolu / Pistonlu	Serve Engine / Piston Servolu / Pistonlu	Serve Engine / Piston Servolu / Pistonlu
Cutting Process Kesme Prosesi	Guillotine Cutting Giyotin Kesim	Guillotine / Punch / Elips Cutting Giyotin / Punch / Elips Kesim	Guillotine / Punch / Elips / Perforation / Mold Cutting Giyotin / Punch / Elips / Perfore / Kalıplı Kesim	Guillotine / Punch / Elips / Perforation / Mold Cutting Giyotin / Punch / Elips / Perfore / Kalıplı Kesim	Mold Cutting Kalıplı Kesim	Guillotine Cutting Giyotin Kesim	Guillotine / Perforation / Mold Cutting Giyotin / Perfore / Kalıplı Kesim
Cooling Water Soğutma Suyu	12 - 16 C / 2500Kcal / hour 12 - 16 C / 2500Kcal / saat	12 - 16 C / 2500Kcal / hour 12 - 16 C / 2500Kcal / saat	12 - 16 C / 2500Kcal / hour 12 - 16 C / 2500Kcal / saat	12 - 16 C / 2500Kcal / hour 12 - 16 C / 2500Kcal / saat	12 - 16 C / 2500Kcal / hour 12 - 16 C / 2500Kcal / saat	12 - 16 C / 2500Kcal / hour 12 - 16 C / 2500Kcal / saat	12 - 16 C / 2500Kcal / hour 12 - 16 C / 2500Kcal / saat
Electrical Values Elektrik Tüketim	Max. 10kW - 380V	Max. 10kW - 380V	Max. 15kW - 380V	Max. 18kW - 380V	Max. 10kW - 380V	Max. 15kW - 380V	Max. 15kW - 380V
Compressed Air Basınçlı Hava	6 - 8 bar 1200L / min.	6 - 8 bar 1200L / min.	6 - 8 bar 1200L / min.	6 - 8 bar 1200L / min.	6 - 8 bar 1200L / min.	6 - 8 bar 1200L / min.	6 - 8 bar 1200L / min.