


Available Range /

Kullanım Aralıkları

Thermoform Packaging
Machines

Termoform Ambalaj Makineleri



	Bpt Jr	Bpt-P Series	Bpt-S Series	Bpt-Y Series	Bpt-Y IML Series
Applications Ürün Tipi	Ketchup, Mayonnaise, Jam, Honey, Sauce, Butter, etc. Ketçap, Mayonel, Reçel, Bal, Sos, Tereyağı, vb.	Ketchup, Mayonnaise, Jam, Honey, Sauce, Butter, etc. Ketçap, Mayonel, Reçel, Bal, Sos, Tereyağı, vb	Water, Water Juice, Lemonade, etc. Su, Meyve Suyu, Limonata, vb.	Yoghurt, Fruit Yoghurt, etc. Yoğurt, Meyveli Yoğurt, vb.	Yoghurt, Fruit Yoghurt, etc. Yoğurt, Meyveli Yoğurt, vb.
Capacity Kapasite	18 - 22 cycle/min. 18 - 22 vuruş/dk.	Piston: 18 - 22 cycle/min. Servo: 24 - 28 vuruş/dk.	Piston: 18 - 22 cycle/min. Servo: 24 - 28 vuruş/dk.	20 - 28 cycle/min. 20 - 28 vuruş/dk.	24 - 25 cycle/min. 24 - 25 vuruş/dk.
Packaging Type	Simple Hermetic	Simple Hermetic	Simple Hermetic	Simple Hermetic	Simple Hermetic
Shape Depth Şekil Derinliği	max. 50mm.	max. 90mm.	max. 90mm.	max. 90mm.	max. 90mm.
Film Widths Film Genişliği	200 - 280mm.	220 - 410mm.	330 - 420mm.	220 - 410mm.	220 - 410mm.
Film Thickness Film Kalınlığı	350 - 700µm.	400 - 1200µm.	350 - 800µm.	600 - 1500µm.	600 - 1500µm.
Bottom Film Alt Film	PVC / PS / PET	PVC / PS / PET	PET	PS	PS
Top Film (customizable) Üst Film (özelleştirilebilir)	AL+OPP / AL	AL+OPP / AL	ALU / ALU+PET	ALU / OPP / MIXPAP/ AL+THERMOLAC	ALU / OPP / MIXPAP/ AL+THERMOLAC
Reel Diameter Bobin Çapları	Bottom: max. 350mm. Top: max. 200mm. Alt: max. 350mm. Üst: max. 200mm.	Bottom: max. 1000mm. Top: max. 300mm. Alt: max. 1000mm. Üst: max. 300mm.	Bottom: max. 1000mm. Top: max. 300mm. Alt: max. 1000mm. Üst: max. 300mm.	Bottom: max. 1000mm. Top: max. 300mm. Alt: max. 1000mm. Üst: max. 300mm.	Bottom: max. 1000mm. Top: max. 300mm. Alt: max. 1000mm. Üst: max. 300mm.
Reel Core Diameter Bobin Göbek Çapı	76mm.	76mm.	76mm.	76mm.	76mm.
Machine Dimensions (approx) Makine Ölçüleri (yaklaşık)	2200x1200x2000mm.	6000x1200x2000mm.	9500x6000mm.	8000x1500x2500mm.	8000x1500x2500mm.
Stations Drive Type İstasyonlar Tahrik Tipi	Piston Pistonlu	Serve Engine / Piston Servolu / Pistonlu	Serve Engine / Piston Servolu / Pistonlu	Serve Engine Servolu	Serve Engine Servolu
Cutting Process Kesme Prosesi	Mold Cutting Kalıplı Kesim	Mold / Perforation Cutting Kalıplı Kesim / Perfore Kesim	Mold Cutting Kalıplı Kesim	Mold / Perforation Cutting Kalıplı Kesim / Perfore Kesim	Mold / Perforation Cutting Kalıplı Kesim / Perfore Kesim
Cooling Water Soğutma Suyu	12 - 16 C / 2500Kcal / hour 12 - 16 C / 2500Kcal / saat	12 - 16 C / 5000Kcal / hour 12 - 16 C / 5000Kcal / saat	12 - 16 C / 6000Kcal / hour 12 - 16 C / 6000Kcal / saat	12 - 16 C / 6000Kcal / hour 12 - 16 C / 6000Kcal / saat	12 - 16 C / 6000Kcal / hour 12 - 16 C / 6000Kcal / saat
Electrical Values Elektrik Tüketim	Max. 15kW - 380V	Max. 15kW - 380V	Max. 18kW - 380V	Max. 18kW - 380V	Max. 18kW - 380V
Compressed Air Basıncılı Hava	6 - 8 bar 1500L / min.	6 - 8 bar 3000L / min.	6 - 8 bar 3000L / min.	6 - 8 bar 3000L / min.	6 - 8 bar 3000L / min.